

KEY BENEFITS**Compact Design**

- Up to 50% less volume and volumetric weight than existing single-use designs*

Reduced Freight Costs

- Substantial savings can be achieved†

Robust performance

- Tested against ISTA 7D for 6+ days throughout the entire product load area (fully mapped)

Universal Pack-Out

- Four sizes available

Premium single-use solution

- Engineered with compact Vacuum Insulation Panels (VIPs) & Advanced PCM gels

Hibernation Capable


- Can hibernate without compromising performance

Eco-Friendly

- Made from VIPs, which significantly reduce GHG emissions, Water and Fossil Fuel Use compared to PUR

*Compared to comparably sized CCT Excel and CCT Extreme models.

†Varies with route and carrier.



Up to 6+ Days



**Controlled Room
Temperature
15°C to 25°C**



**Frozen
-15°C to -25°C**



**Universal Pack-Out
Four sizes
3L to 59L**



**Refrigerated
2°C to 8°C**



**Dry Ice
-70°C and below**

Configurations Available

Configurations Available	
Partially Assembled with product box assembled	Outer corrugate, VIP insulation, risers if needed, PCM in cases, temperature label
Fully Assembled but not conditioned (sent in protective outer corrugate box)	Ready to be conditioned and to receive product load

CCT Advanced™ SU



REFRIGERATED (2.0°C to 8.0°C) & CONTROLLED ROOM TEMP (15.0°C to 25.0°C)

Part Number	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight
		Length	Width	Height		
ADV-96-SM-RFG ADV-96-SM-CRT	Payload	7 5/8 in (194 mm)	7 5/8 in (194 mm)	6 1/8 in (156 mm)	5.8 L	21.4 lbs (9.7 kg)
	Outside	13 11/16 in (348 mm)	13 11/16 in (348 mm)	12 11/16 in (322 mm)		
ADV-96-MD-RFG ADV-96-MD-CRT	Payload	15 5/8 in (397 mm)	7 5/8 in (194 mm)	7 1/8 in (181 mm)	13.9 L	34.2 lbs (15.5 kg)
	Outside	21 11/16 in (551 mm)	13 11/16 in (348 mm)	13 11/16 in (348 mm)		
ADV-96-LG-RFG ADV-96-LG-CRT	Payload	15 3/8 in (391 mm)	15 3/8 in (391 mm)	6 7/8 in (175 mm)	26.8 L	51.7 lbs (23.5 kg)
	Outside	21 5/8 in (549 mm)	21 5/8 in (549 mm)	14 in (356 mm)		
ADV-96-XL-RFG ADV-96-XL-CRT	Payload	15 3/8 in (391 mm)	15 3/8 in (391 mm)	13 7/8 in (353 mm)	53.7 L	73.0 lbs (33.1 kg)
	Outside	21 5/8 in (549 mm)	21 5/8 in (549 mm)	21 in (533 mm)		



FROZEN (-15.0°C to -25.0°C)

Part Number	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight
		Length	Width	Height		
ADV-96-SM-FRZ	Payload	5 7/8 in (149 mm)	5 7/8 in (149 mm)	4 1/3 in (110 mm)	2.5 L	27.3 lbs (12.4 kg)
	Outside	13 2/3 in (348 mm)	13 2/3 in (348 mm)	12 2/3 in (322 mm)		
ADV-96-MD-FRZ	Payload	13 7/8 in (352 mm)	5 7/8 in (149 mm)	5 1/3 in (136 mm)	7.1 L	43.8 lbs (19.9 kg)
	Outside	21 11/16 in (551 mm)	13 11/16 in (348 mm)	13 11/16 in (348 mm)		
ADV-96-LG-FRZ	Payload	13 3/4 in (349 mm)	13 3/4 in (349 mm)	5 in (130 mm)	15.8 L	67.2 lbs (30.0 kg)
	Outside	21 5/8 in (549 mm)	21 5/8 in (549 mm)	14 in (356 mm)		
ADV-96-XL-FRZ	Payload	13 3/4 in (349 mm)	13 3/4 in (349 mm)	11 4/5 in (300 mm)	35.5 L	96.1 lbs (44.0 kg)
	Outside	21 5/8 in (549 mm)	21 5/8 in (549 mm)	21 in (533 mm)		



DRY ICE (-70.0°C and below)

Part Number	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight
		Length	Width	Height		
ADV-96-SM-DI	Payload	5 7/8 in (149 mm)	5 7/8 in (149 mm)	4 1/3 in (110 mm)	2.8 L	28.1 lbs (12.7 kg)
	Outside	13 2/3 in (348 mm)	13 2/3 in (348 mm)	12 2/3 in (322 mm)		
ADV-96-MD-DI	Payload	13 7/8 in (352 mm)	5 7/8 in (149 mm)	5 1/3 in (136 mm)	9.0 L	46.8 lbs (21.2 kg)
	Outside	21 11/16 in (551 mm)	13 11/16 in (348 mm)	13 11/16 in (348 mm)		
ADV-96-LG-DI	Payload	14 1/6 in (360 mm)	14 1/6 in (360 mm)	5 1/2 in (140 mm)	18.0 L	71.0 lbs (32.0 kg)
	Outside	21 5/8 in (549 mm)	21 5/8 in (549 mm)	14 in (356 mm)		
ADV-96-XL-DI	Payload	13 3/4 in (349 mm)	13 3/4 in (349 mm)	11 4/5 in (300 mm)	41.0 L	96.1 lbs (44.0 kg)
	Outside	21 5/8 in (549 mm)	21 5/8 in (549 mm)	21 in (533 mm)		



ColdChainTech.com



Global Headquarters

Tel: (508) 429-1395
Fax: (508) 429-9056
Toll-Free: (800)-370-8566

info@coldchaintech.com

Panama & South America

Tel 1: +507-6506-7384
Tel 2: +507-830-0705
Tel 3: +1-508-333-5888

cct-latam@coldchaintech.com

Europe, Middle East, & Africa

Customer Services: +31 6 2137 2929
Sales: +44-7497-085-117

emea@coldchaintech.com

Singapore & Asia Pacific

Customer Services: +65 6818 6204
Sales: +65 6818 6203

cct-ap@coldchaintech.com

All rights reserved. Copyright ©2023