

Cold Chain Assurance for Specialty Pharmacies

KEY BENEFITS

Duration

36+ hours of performance

ISTA 7E Qualified

Qualified for Refrigerated, Room Temperature and Frozen shipments

Simple, Seasonal Pack-outs

Hot, Cold and Moderate Pack-outs

Single Refrigerant

One refrigerant across all seasons and sizes

Compliance Assistance

Performance qualification (PQ) study kits available

Documentation for accreditation audits



Controlled Room Temperature
15.0°C to 25.0°C



Frozen
<20°C



Refrigerated
2.0°C to 8.0°C



Seasonal Pack-Out
Four sizes: 2L to 15L



36+ Hours



CCT Smart Solutions
Route Pro Application

Lid Assembly



Product Box

Gel Refrigerant



CONFIGURATIONS AVAILABLE

CISU-BD (Bundle)

Insulated shippers in outer corrugate shipped on pallet. Refrigerant cases are not included.

PT (Pallet)

Insulated shippers in outer corrugate shipped on a pallet. Refrigerant cases are included.

PCL (Parcel)

Insulated shippers in outer corrugate shipped with 1 case of 620E-SP refrigerants.

CCT RX

CCT Rx SMALL									
Part Number	Temp Profile	Duration (hr)	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight lbs (kg)	Volumetric Weight lbs (kg)
				Length	Width	Height			
RX-36-SM-XX	ALL		Outside	11.81" (300 mm)	9.81" (249 mm)	10.74" (273 mm)			10 (4.5 kg)
	RFG-HOT	36+	Payload	7.5" (191 mm)	5.5" (140 mm)	1.5" (38 mm)	1L	5 lbs. (2.3 kg)	
	RFG-MOD	36+	Payload	6.25" (159 mm)	5.5" (140 mm)	1.25" (32 mm)	.7L	5 lbs. (2.3 kg)	
	RFG-COLD	36+	Payload	7.5" (191 mm)	5.5" (140 mm)	3.25" (83 mm)	2.2L	3.8 lbs. (1.7 kg)	
	CRT-HOT	36+	Payload	7.5" (191 mm)	5.5" (140 mm)	2.5" (64 mm)	1.4L	6.2 lbs. (2.8 kg)	
	CRT-MOD	36+	Payload	7.5" (191 mm)	5.5" (140 mm)	2.63" (67 mm)	1.7L	3.8 lbs. (1.7 kg)	
	CRT-COLD	36+	Payload	7.5" (191 mm)	5.5" (140 mm)	4.75" (121 mm)	3.1L	6.3 lbs. (2.8 kg)	
	FROZEN	36+	Payload	6.25" (159 mm)	4.75" (121 mm)	1.5" (38 mm)	.8L	9.9 lbs. (4.5 kg)	

CCT Rx MEDIUM									
Model Number	Temp Profile	Duration (hr)	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight lbs (kg)	Volumetric Weight lbs (kg)
				Length	Width	Height			
RX-36-MD-XX	ALL		Outside	12.38" (314 mm)	10.38" (263 mm)	11.75" (275 mm)			13 (5.9 kg)
	RFG-HOT	36+	Payload	7.5" (191 mm)	7.5" (191 mm)	1.75" (44 mm)	1.6L	6 lbs. (2.7 kg)	
	RFG-MOD	36+	Payload	7.5" (191 mm)	7.5" (191 mm)	1.25" (32 mm)	1.2L	6 lbs. (2.7 kg)	
	RFG-COLD	36+	Payload	7.5" (191 mm)	7.5" (191 mm)	3.75" (95 mm)	3.5L	4.7 lbs. (2.1 kg)	
	CRT-HOT	36+	Payload	7.5" (191 mm)	7.5" (191 mm)	3.5" (89 mm)	3.2L	9.8 lbs. (4.5 kg)	
	CRT-MOD	36+	Payload	7.5" (191 mm)	7.5" (191 mm)	4" (102 mm)	3.7L	7.3 lbs. (3.3 kg)	
	CRT-COLD	36+	Payload	7.5" (191 mm)	7.5" (191 mm)	4.63" (117 mm)	4.3L	8.6 lbs. (3.9 kg)	
	FROZEN	36+	Payload	6.25" (159 mm)	4.5" (114 mm)	4.75" (121 mm)	2.2L	11.4 lbs. (5.2 kg)	

CCT RX

CCT Rx LARGE

Model Number	Temp Profile	Duration (hr)	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight lbs (kg)	Volumetric Weight lbs (kg)
				Length	Width	Height			
RX-36-LG-XX	ALL		Outside	15.81" (416 mm)	13.69" (365 mm)	12.63" (321 mm)			15 (6.8 kg)
	RFG-HOT	36+	Payload	11.5" (292 mm)	9.5" (241 mm)	3.5" (89 mm)	6.3L	13.7 lbs. (6.2 kg)	
	RFG-MOD	36+	Payload	11.5" (292 mm)	9.5" (241 mm)	3.5" (89 mm)	6.3L	13.7 lbs. (6.2 kg)	
	RFG-COLD	36+	Payload	11.5" (292 mm)	9.5" (241 mm)	5.75" (146 mm)	10.3L	11.2 lbs. (5.1 kg)	
	CRT-HOT	36+	Payload	11.5" (292 mm)	9.5" (241 mm)	4.5" (114 mm)	8.1L	11.1 lbs. (5 kg)	
	CRT-MOD	36+	Payload	11.5" (292 mm)	9.5" (241 mm)	6.75" (171 mm)	12.1L	7.3 lbs. (3.3 kg)	
	CRT-COLD	36+	Payload	11.5" (292 mm)	9.5" (241 mm)	5.63" (143 mm)	10.1L	11.1 lbs. (5 kg)	
	FROZEN	36+	Payload	9.5" (241 mm)	7.5" (191 mm)	6.25" (159 mm)	7.4L	19.5 lbs. (8.9 kg)	

CCT Rx EXTRA LARGE

Model Number	Temp Profile	Duration (hr)	Dimension Type	Approximate Dimensions			Payload Volume	Tare Weight lbs (kg)	Volumetric Weight lbs (kg)
				Length	Width	Height			
RX-36-XL-XX	ALL		Outside	22" (559 mm)	14.06" (357 mm)	14.69" (373 mm)			31 (14.1 kg)
	RFG-HOT	36+	Payload	13.5" (434 mm)	8.75" (222 mm)	6.25" (159 mm)	12.1L	13.6 lbs. (6.2 kg)	
	RFG-MOD	36+	Payload	16.5" (429 mm)	7.5" (191 mm)	5.25" (133 mm)	10.6L	11.1 lbs. (5 kg)	
	RFG-COLD	36+	Payload	16.5" (429 mm)	8.75" (222 mm)	7" (178 mm)	16.6L	11.1 lbs. (5 kg)	
	CRT-HOT	36+	Payload	16.5" (429 mm)	8.75" (222 mm)	6.5" (165 mm)	15.4L	13.6 lbs. (6.2 kg)	
	CRT-MOD	36+	Payload	16.5" (429 mm)	8.75" (222 mm)	6.75" (171 mm)	16L	11.1 lbs. (5 kg)	
	CRT-COLD	36+	Payload	16.5" (429 mm)	8.75" (222 mm)	7.75" (197 mm)	18.3L	12.3 lbs. (5.6 kg)	
	FROZEN	36+	Payload	14.25" (362 mm)	7.5" (191 mm)	6.25" (159 mm)	10.9L	22.1 lbs. (10 kg)	



ColdChainTech.com



Global Headquarters
Cold Chain Technologies
Franklin, MA

info@coldchaintech.com

Panama & South America
Cold Chain Technologies de Panama
Sao Paulo, Brazil

cct-latam@coldchaintech.com

Europe, Middle East, & Africa
Cold Chain Technologies B.V.
The Netherlands

emea@coldchaintech.com

Singapore & Asia Pacific
Cold Chain Technologies Asia Pte. Ltd.
Singapore

apac@coldchaintech.com

To learn more about our locations, kindly visit coldchaintech.com/global-locations
All rights reserved. Copyright ©2024